

PRODUCT DATA SHEET

WALL AND FIREPLACE CONNECTION

PRODUCT DESCRIPTION

The self-adhesive wall and fireplace connection provides a **simple, secure roof connection**. The lead-free strip is made from a structured aluminium sheet and dyed with polyester paint. Not only can the product be used for sealing between the wall or fireplace and roof surface, but it is also ideal for **weatherproofing around chimneys, exterior walls and roof windows**. The universal product, dyed with polyester paint, is available in two colours: brick red and black.

ADVANTAGES

- Perfectly adheres to each surface
- Resists long-term weather conditions such as UV radiation, frost, rain, snow, moisture, and ageing processes
- Easy to install thanks to the pleating/stretching (high adhesive strength)
- Immediately seals the surface
- Resists ageing very well
- Different strip widths allow you to choose the right strips for the job.
- Can also be ordered with rounded edges to prevent cut injuries to hands
- Universally usable

SPECIFICATIONS

- Aluminium material: Aluminium thickness 0.10 mm
- Butyl adhesive: approx. 0.9 – 1.0 mm, high adhesive strength
- Butyl sealant: approx. 1.35 g/ml / high adhesive strength
- Temperature resistance: -30 to + 90 °C
- Processing temperature: +5 to + 40 °C
- UV protection: The product is not affected by environmental factors

APPLICATION

- Seal the roof connections to the fireplace, ceiling or the wall
- Seal the bay and roof windows

MATERIAL

- Aluminium



PRODUCT DATA SHEET

WALL AND FIREPLACE CONNECTION

ROLL SIZE

- Roll width: 300 mm
- Roll length: 5000 mm

STORAGE

Store in a cool and dry place.



HEALTH AND SAFETY RECOMMENDATIONS

Follow the general rules of occupational hygiene when using chimney sealing strips.

PRODUCT TABLE

Wall and fireplace connection

Art. no.	Dimensions ^{a)} [mm]	Colour [mm]	PU
954219	30000 x 5000	Black (RAL 9005)	1
954220	30000 x 5000	Red (RAL 8004)	1

a) Width x length



INSTRUCTION FOR USE

Thanks to its structured aluminium sheet and special pyramid shape, the self-adhesive wall connection tape can be easily shaped. The self-adhesive side of the product is fully coated with butyl adhesive, which facilitates assembly even more while ensuring a perfect bond with the roof covering.

The lead-free aluminium wall and fireplace connection is easy to install in just a few steps. It is easy to cut to size, shape and press in by hand using a robust pair of scissors or a cutting knife.

The durability of the entire roof construction is guaranteed by the weather resistance, colour stability and UV resistance of the wall and fireplace connection.

If you are not familiar with this product's application, and particularly with the product's intended use, please contact our Application Technology department (technik@eurotec.team).