PRODUCT DATA SHEET

T-PROFILE

PRODUCT DESCRIPTION

Eurotec's T-profile is a hidden aluminium wood connector for use both indoors and outdoors. Suitable in terms of geometry for right-angled and inclined connections of individual beams in wood / wood and wood / concrete applications. Can be combined with our rod dowel, which is screwed in through the T-profile as part of a selfdrilling process.

APPLICATIONS

· Conditionally corrosion-resistant and suitable for use in service classes 1, 2 and 3 according to DIN EN 1995 (Eurocode 5)

MATERIAL

- · High-quality aluminium
- · Available in a length of 2.00 m
- · Measurement scale for individual profile cutting on the construction site



CERTIFICATION

• European standard EN 1090-1



CERTIFICATION

· Certification ETA 21/0710 in combination with the EST rod dowel in the T-Tec system

PRODUCT TABLE


T-Profile				
Art. no.	Dimensions [mm]	Material thickness [mm]	Material	PU
975652	115 x 2000 x 80	6	Aluminium	1


© by E.u.r.o.Tec GmbH \cdot Last updated 03/2024 \cdot Subject to changes, additions, typesetting and printing errors.

PRODUCT DATA SHEET

T-PROFILE

TECHNICAL INFORMATION





INSTRUCTIONS FOR USE

- 1. No need for pre-drilling with the self-drilling EST rod dowel (Ø 7.5)
- 2. Hole pattern for the 5.0 x 50 mm angle-bracket screw
- 3. Rock concrete screw (Ø 7.5) for the wood / concrete joint

If you are not familiar with how this product is used, and particularly with the product's intended use, please contact our Application Technology department (Technik@eurotec.team).