

# PRODUCT DATA SHEET

## SL PRO ADJUSTABLE PEDESTALS

### PRODUCT DESCRIPTION

The Eurotec SL PRO M and L adjustable pedestals are suitable for installing deck substructures in outdoor applications.

The top of the pedestal is freely adjustable and self-leveling, which means that an uneven floor with a gradient up to 8 % can be compensated. The key benefit of the SL PRO is that no additional pedestals or setups are needed for it to work properly.

The self-leveling pedestal can be used as drainage as well. It can create a small slope of 1 – 2 % so water can run freely.



### APPLICATIONS / ADVANTAGES

- Self-leveling up to 8 % (4,56°) slope
- Freely adjustable height of 55 to 102 mm
- Combinable with L adapter
- Combinable with Click adapter
- Combinable with the Extension rings +4 and +10 cm



#### Notes

Individual support is not recommended is not recommended, as there is a risk that the SL PRO will not be able to maintain the inclination, resulting in unintentional movement.

### SPECIFICATIONS

- UV stability
- High creep rupture strength
- Very good chemical resistance
- Acoustic damping properties

### MATERIAL

- Polypropylen-Copolymer (PP-C)

# PRODUCT DATA SHEET

## SL PRO ADJUSTABLE PEDESTALS

### PRODUCT TABLE

Adjustable Pedestal SL Pro				
Art.-No.	Name	Assembly height* [mm]	Load bearing capacity [kN]	PU
946071-SL	SL PRO M	55 - 84	8,0	10
946072-SL	SL PRO L	73 - 102	8,0	10

a) The assembly height can only be reached with the fitting adapters.

If there is risk of impact vibration on the decking, the decking pedestals should be secured in place. In addition, decking pedestals that are frequently subject to stresses should be secured by screws to avoid twisting.