

ROUND SLINGS

ROUND SLINGS, BEARING CAPACITY 1000 KG

SPECIFICATIONS / ADVANTAGES

- In accordance with EN 1492-2
- For lifting fragile loads
- Double-woven tubular sheath made of polyester fabric, core made of polyester yarn
- High bearing capacity
- Low dead weight
- Wide bearing surface
- Colour coding to EU standard
- Barrel stripes sewn in
- Bearing capacity (WLL — Working Load Limit) printed on



ROUND SLINGS, BEARING CAPACITY 1000 KG				
ART. NO.	DIMENSIONS	SCOPE [M]	LOADBEARING CAPACITY [KG]	PU
324040	1 m x 50 mm	2	1000	1
324070	1,5 m x 50 mm	3	1000	1

ROUND SLINGS, BEARING CAPACITY 2000 KG

SPECIFICATIONS / ADVANTAGES

- In accordance with EN 1492-2
- For lifting fragile loads
- Double-woven tubular sheath made of polyester fabric, core made of polyester yarn
- High bearing capacity
- Low dead weight
- Wide bearing surface
- Colour coding to EU standard
- Barrel stripes sewn in
- Bearing capacity (WLL — Working Load Limit) printed on



ROUND SLINGS, BEARING CAPACITY 2000 KG				
ART. NO.	DIMENSIONS	SCOPE [M]	LOADBEARING CAPACITY [KG]	PU
324060	1 m x 55 mm	2	2000	1
324080	1,5 m x 55 mm	3	2000	1
324050	2 m x 55 mm	4	2000	1

ROUND SLINGS, BEARING CAPACITY 3000 KG

SPECIFICATIONS / ADVANTAGES

- In accordance with EN 1492-2
- For lifting fragile loads
- Double-woven tubular sheath made of polyester fabric, core made of polyester yarn
- High bearing capacity
- Low dead weight
- Wide bearing surface
- Colour coding to EU standard
- Barrel stripes sewn in
- Bearing capacity (WLL — Working Load Limit) printed on



ROUND SLINGS, BEARING CAPACITY 3000 KG				
ART. NO.	DIMENSIONS	SCOPE [M]	LOADBEARING CAPACITY [KG]	PU
324100	2 m x 65 mm	4	3000	1

If you are not familiar with how this product is used, and particularly with the product's intended use, please contact our Application Technology department (technik@eurotec.team).