

## Product data sheet – Adjustable Pedestal SL Pro

### Product description

The Eurotec SL PRO M and L adjustable pedestals are suitable for installing deck substructures in outdoor applications.

The top of the pedestal is freely adjustable and self-leveling, which means that an uneven floor with a gradient up to 8 % can be compensated. The key benefit of the SL PRO is that no additional pedestals or setups are needed for it to work properly.

The self-leveling pedestal can be used as drainage as well. It can create a small slope of 1 – 2 % so water can run freely.



### Material

- Polypropylen-Copolymer (PP-C)

### Advantages

- Self-leveling up to 8 % (4,56°) slope
- Freely adjustable height of 55 to 102 mm
- Combinable with L adapter
- Combinable with the Extension rings +4 and +10 cm

### Specifications

- UV stability
- High creep rupture strength
- Very good chemical resistance
- Acoustic damping properties

## Product data sheet – Adjustable Pedestal SL Pro

## Article table

Adjustable Pedestal SL Pro				
Art.-No.	Name	Assembly height* [mm]	Load bearing capacity [kN]	PU
946071-SL	SL PRO M	55 - 84	8,0	10
946072-SL	SL PRO L	73 - 102	8,0	10

a) The assembly height can only be reached with the fitting adapters.

## Application note



If there is risk of impact vibration on the decking, the decking pedestals should be secured in place. In addition, decking pedestals that are frequently subject to stresses should be secured by screws to avoid twisting.

If you are not familiar with the application of the product at hand, especially with the handling according to given regulations, it is essential to get in contact with our technical application support department (Technik@eurotec.team).

Page 2 of 2