

PRODUCT DATA SHEET

PRODUCT DESCRIPTION

The PRO adjustable pedestals are suitable for **timber decks** and **stone patios** with **various assembly heights**.

The Profi-Line series of adjustable pedestals from Eurotec provides you with a modular system: innovative, universal, versatile and user-friendly!

The series comprises **six** adjustable pedestals of **different heights**. Their assembly heights can be altered with extension rings or extension plates.

ADVANTAGES

- High load-bearing capacity of 8.0 kN/pedestal
- Base assembly heights of 10 – 168 mm
- Height can be increased with extension ring or extension plate
- Quick and easy assembly
- Stepless height adjustment
- Resistant to weather, exposure to UV, insects and rot

APPLICATION IMAGE



Deck substructure with Profi-Line adjustable pedestals

PROFI-LINE ADJUSTABLE PEDESTALS



PRO S

PRO XL



Preparation of a substructure with Profi-Line adjustable pedestals

PRODUCT DATA SHEET

PROFI-LINE ADJUSTABLE PEDESTALS

PRODUCT TABLE PROFI-LINE ADJUSTABLE PEDESTALS

| Art. no. | Product name | Material | Assembly height [mm] | Load-bearing capacity* [kN] | PU |
|----------|---------------------|----------|----------------------|-----------------------------|----|
| 954020 | PRO XXS** | PP-C | 10 – 15 | 4,0 | 50 |
| 954021 | Extension plate XXS | PP-C | 5 | 4,0 | 50 |
| 954061 | PRO XS** | PP-C | 22 – 30 | 8,0 | 20 |
| 946070 | PRO S | PP-C | 30 – 53 | 8,0 | 10 |
| 946071 | PRO M | PP-C | 53 – 82 | 8,0 | 10 |
| 946072 | PRO L | PP-C | 70 – 117 | 8,0 | 10 |
| 946079 | PRO XL | PP-C | 74 – 168 | 8,0 | 10 |

*The specified value of the load capacity represents recommended values. Under these loads, the adjustable pedestals deform by only approx. 2 mm.
The load-bearing capacity up to the actual breakage is many times higher.

**Comes with both an L adapter and stone adapter.

Note: The adapters for the XXS/XS adjustable pedestals are only suitable for the XXS/XS and cannot be combined with the rest of the PRO family. Not compatible with the Nivello 2.0.

PRODUCT DATA SHEET

ACCESSORIES – ADAPTER

The series of adjustable pedestals is completed by three different types of adapter:

L adapter – for classic timber substructures or modern aluminium substructures

Click adapter – for clicking Eurotec aluminium profiles into place in a time-saving manner

Stone adapter – for laying stone slabs

The PRO XXS/XS comes with L adapter and stone adapter.

The PRO adjustable pedestals can therefore be adapted to your individual requirements and construction-site circumstances in a quick and straightforward manner.

Note: The adapters for the XXS/XS adjustable pedestals are only suitable for the XXS/XS and cannot be combined with the rest of the PRO family. Not compatible with the Nivello 2.0.

PROFI-LINE ADJUSTABLE PEDESTALS



L adapter



Stone adapter



Click adapter 40



Click adapter 60

APPLICATION IMAGE



Adjustable pedestal PRO M with click adapter and EVO aluminium system profile



Single point support stone patio: PRO S with stone adapter

PRODUCT DATA SHEET

PROFI-LINE ADJUSTABLE PEDESTALS

ACCESSORIES – EXTENSION RINGS

For increasing the height of the PRO adjustable pedestals.

Suitable for the:

PRO S, M, L und XL as well as SL PRO M and L



Extension ring +4



Extension ring +10

PRODUCT TABLE PROFI-LINE ADJUSTABLE PEDESTALS ACCESSORIES

| Art. no. | Product name | Material | Assembly height [mm] | Load-bearing capacity* [kN] | PU |
|----------|--------------------|----------|----------------------|-----------------------------|----|
| 946075 | L adapter | PP-C | - | - | 10 |
| 946076 | Click adapter 40 | PP-C | - | - | 10 |
| 946077 | Click adapter 60 | PP-C | - | - | 10 |
| 946078 | Stone adapter | PP-C | - | - | 10 |
| 946069 | Extension ring +2 | PP-C | 20 | 8,0 | 40 |
| 946074 | Extension ring +4 | PP-C | 40 | 8,0 | 10 |
| 946073 | Extension ring +10 | PP-C | 100 | 8,0 | 10 |

*The specified value of the load capacity represents recommended values. Under these loads, the adjustable pedestals deform by only approx. 2 mm. The load-bearing capacity up to the actual breakage is many times higher.

FURTHER IMPORTANT INFORMATION

The adjustable pedestals are suitable for predominantly static centric compressive loading in multiple-supported systems.

In case of risk of vibration on the terrace adjustable pedestals should be able to be secured. Furthermore, they should be charged in high frequency by means of a screw secured against twisting.

Observe the manufacturer's instructions for the support of the stone slabs! The use of our system does not release planners/processors from informing themselves about the manufacturer's specifications of other products (installed together with our system).

If you are not familiar with how this product is used, and particularly with the product's intended use, please contact our Application Technology department (technik@eurotec.team).